

UNIQUE DESIGN
FOR LAB LIFE
LABOPORT®
VACUUM PUMPS
N 96 I N 820 G I N 840 G



AN EYE FOR DETAIL

RETHINKING EVERYDAY LAB PRACTICE

What aspects do you believe are key when using vacuum pumps in everyday lab practice? What does it take to create simple, economical processes that are reliable day in, day out? And what makes work enjoyable?

These are the questions we used as a guide when redesigning our successful laboratory pump series LABOPORT. We became involved in daily lab work, asking users what they wished for, enlisting experts to perform tests and incorporating their suggestions.

The result? Clever, elegant design with clear benefits in terms of handling and functionality.



WE KNOW WHAT COUNTS

UNIQUE DESIGN, EASE OF USE

■ Exceptionally space saving

The impressively compact device takes up little space.

Easy to clean

The smooth surfaces without any ribs or hard edges are easy to keep clean.

ATEX-compliant and chemically resistant for very aggressive/ corrosive gases

The inner, wetted area has been equipped to transfer explosive atmospheres.



Speed-controlled

The speed can be controlled by simply manually adjusting the vacuum power using the control knob or via an interface by connecting the pump to KNF's VC 900 controller. Ideal for combining with all common vacuum controllers with valve control.



3-color status display


The changing color display allows the operational status to be ascertained at a glance. (1)

(2)

(2)

Blue: in operation

Green: stand-by



Red: error



Expandable Separators and/or condensers can be purchased individually at any time and easily fitted, enabling users to build their own customized vacuum system. Integrated gas ballast valve This valve supports short processing times even with solvents





The fold-out handle makes the device easy to transport and store.



















with a high boiling point, which

protects the pump head.





















TECHNICAL DATA

AN ALL-ROUNDER IN THE LAB



		LABOPORT® N 96	LABOPORT® N 820 G Il 2/-G IIB+H2 T3 internal atmosphere only	LABOPORT® N 840 G S II 2/-G IIB+H2 T3 internal atmosphere
APPLICATION	Filtration	Х		Х
	SPE	Х		
	Degassing		X	
	Fluid aspiration	Х	Х	
	Gel drying		X	
	Rotary evaporation		Х	Х
	Centrifugal concentration			Х
	Flow rate (m³/h) at atm. pressure	0.4	1. 2	2.04
	Ultimate vacuum (mbar abs.)	<130	6	6
Ψ	Operating pressure (bar)	2.5	0.1	0.1
TECHNICAL DATA	Hose connections (mm)	NPT 1/8 – ID6, PP	ID 9.5-8, PVDF	ID 9.5-8, PVDF
	Permissible media and ambient temperature	+5 + 40 °C	+5+40°C	+5 + 40 °C
H	Integrated gas ballast valve	No	Yes	Yes
Ĕ	Integrated rotational speed control	Yes	Yes	Yes
	Weight (kg)	1.3	8.8	11.3
	Dimensions W x H x D (mm)	156 x 119 x 75	163 x 220 x 259	177 x 240 x 289
MATERIAL	Pump head	PPS	PTFE	PTFE
	Diaphragm	PTFE-coated	PTFE-coated	PTFE-coated
	Valves	FKM	FFPM	FFPM
ACCESSORIES	Column fixture	Order no. 323484		

ATEX KEY FOR LABOPORT N 820 G AND N 840 G AND THE TRANSFERABLE, EXPLOSIVE GASES AND VAPORS:

	⟨ II 2/-G IIB+H2 T3 INTERNAL ATMOSPHERI	E ONLY	
	T1	T2	Т3
	methane		
IIA	acetone, ammonia, benzene (pure), acetic acid, ethane, ethyl acetate, carbon oxide, methanol, propane, toluene	ethyl alcohol, n-butane, n-butyl alcohol	gasolines, diesel fuel, aviation fuel, fuel oils, n-hexane
IIB	town gas	ethene	
IIC	hydrogen		•

6

reserves the right to make technical changes without notice. Errors and omissions excepted. KNF 12/2019

YOUR LOCAL PARTNER AROUND THE WORLD

KNF SALES ORGANIZATION

Australia KNF Regional Office Moreland West VIC 3055 Tel. +61 3 9386 4959 info@knf.com.au www.knf.com.au

Benelux Netherlands KNF Verder B.V.

3451 GG Vleuten
Tel. +31 30 677 92 40
info@knf-verder.nl
www.knf-verder.nl

Benelux Belgium and Luxemburg

KNF Verder N.V. 2630 Aartselaar Tel. +32 3 871 96 24 info@knf.be www.knf.be

China KNF Technology (Shanghai) Co., Ltd.

Shanghai 201203
Tel. +86 21 5109 9695
info.cn@knf.com
www.knf.com.cn

France KNF Neuberger SAS

68128 Village-Neuf
Tel. +33 389 70 35 00
info.fr@knf.com
www.knf.fr

Germany KNF Neuberger GmbH

79112 Freiburg Tel. +49 7664 5909 0 info.de@knf.com www.knf.de India KNF Pumps + Systems (India) Pvt. Ltd.

Pimpale Nilakh, Pune 411 027
Tel. +91 82 370 08 923
info.in@knf.com
www.knfpumps.in

Italy KNF Italia S.r.l.

20063 Cernusco s. Naviglio (MI) Tel. +39 02 929 04 91 info.it@knf.com www.knf.it

Japan KNF Japan Co. Ltd.

Tokyo 104-0033
Tel. +81 3 3551 7931
info.jp@knf.com
www.knf.co.jp

Korea KNF Neuberger Ltd.

135-502 Seoul Tel. +82 2 959 0255 knf@knfkorea.com www.knfkorea.com

Latin America KNF Regional Office

Tel. +1 609 649 1010 gb@knf.com www.knf.com/es

Morocco, Tunisia, Algeria

KNF Neuberger SAS 68128 Village-Neuf Tel. +33 389 70 35 00 info.fr@knf.com www.knf.fr **Singapore** KNF Regional Office

Tel. +65 9722 1994 info@knf.com.sg www.knf.com.sg

Sweden, Finland, Denmark, Norway

KNF Neuberger AB 117 43 Stockholm Tel. +46 8 744 51 13 info@knf.se www.knf.se

Switzerland KNF Neuberger AG

8362 Balterswil Tel. +41 71 973 99 30 info.ch@knf.com www.knf.ch

UK, Ireland KNF Neuberger U.K., Ltd. Witney, Oxfordshire OX28 4FA

Tel. +44 1993 77 83 73 info.uk@knf.com www.knf.co.uk

USA, Canada KNF Neuberger, Inc.

Trenton, NJ 08691-1810 Tel. +1 609 890 8600 knfusa@knf.com www.knfusa.com

KNF PRODUCT CENTERS

Gas Pumps KNF Neuberger GmbH

DE-79112 Freiburg info.de@knf.com www.knf.de Liquid Pumps KNF Flodos AG

CH-6210 Sursee info.flodos@knf.com www.knf-flodos.ch